

## BG-Commander-Jr JOYSTICK CONTROLLER

### Universal Compact Serial and IP PTZ Camera Joystick Controller (IP/RS232/422)


Introducing the BG-Commander-Jr, the compact yet powerful professional-grade joystick controller designed to meet the demands of a variety of applications. With its 2-axis joystick and zoom bridge key design, this controller provides refined control, durability, and stability, ensuring smooth and precise camera movement.

The BG-Commander-Jr sets itself apart with its 7-level PTZ speed control, providing operators with complete control over their camera movements with a visual indicator to show the current speed level. Image parameters such as exposure and gain are easily adjustable with knob-style controls and their own small displays showing current value for easy reference.



## FEATURES

- Portable and can be strategically placed
- 4 color LED multi-screen display
- Separated Pan/Tilt joystick and zoom keys for better control and reliability
- 7-level PTZ speed control with visual indicator
- One-button click for auto, manual, and OPT focus modes
- Wide compatibility allows for control of most PTZ cameras
- Password settings available
- Support for up to 2048 devices to add
- Shows preset set, call, & reset in real-time on the main display screen



# Specifications

## Communication and Control Interface

### **RS422/RS485 Interface:**

Phoenix Contact 4 pin 3.81mm Terminal

**RS232C Interface:** DB9 Male Interface

**LAN Interface:** RJ45 Female Interface

**Power Supply:** JEITA Type 4 Female Interface

**Upgrade Online:** Micro USB Female Interface

## Camera Control and Operation

**Supported number of cameras:** 5

**Communication Protocol:** VISCA, PELCO P/D, UDP

**Number of LED Displays:** 4 Units Color LED Display Screen

**Number of Camera Channels:** 5

**Variable knobs:** 4

**Joystick:** 2-Axis

**Zoom Mode:** Tele-Wide Bridge Keys

**Buttons:** 17 Silicon Button

**Presets Short keys:** 5 Presets per Each channel

**Focus Mode:** Auto / Manual / OPT

**Pan/Tilt Rotation Speed:** 7-Level Adjustment

**Zoom In/Out Speed:** 7-Level Adjustment

**AE Mode / WB Mode:**

The mode can be switched arbitrarily, and the value can be adjusted

## Control Signal Format

**Baud Rate:** 2400bps, 4800bps, 9600bps, 19200bps, 38400bps

**Date Bits:** 8 Bit

**Stop Bit:** 1 Bit

**Parity bit:** NONE

**Internet Protocol:** UDP / VISCA OVER IP

**Power Supply and Consumption:**

Rated Voltage DC 12V

Rated Current 0.3A max

**Max Power Consumption:** 3.6W

## Physical and Misc.

**Password Privacy Protection:** YES

**Kingston's Lock Holes:** YES

**Working Temperature:** 32°F ~ 104°F / 0°C ~ 40°C

**Storage Temperature:** -4°F ~ 140°F / -20°C ~ +60°C

**Working Environment:** Indoor

**Dimensions (L x W x H):**

9.6 x 6.5 x 1.9in [244 x 164 x 48mm]

**Gross Weight:** 2.43 lbs [1.1 kg]

## Industry-Leading Warranty & Support

BZBGear Pro AV products and Cameras come with a three-year warranty. An extended two-year warranty is available for our Cameras upon registration for a total of five years. We pride ourselves in our Customer Service and seven-days-a-week Tech Support.

**LIFETIME  
PRODUCT SUPPORT**

PRO AV	CAMERAS
<b>3</b>	<b>5</b>
YEAR WARRANTY	YEAR WARRANTY